

Elite Master

Heavy Duty Warehouse Steps

Welded ribbed aluminium folding ladder with platform, Guardrail and Handrail for professional use. This professional heavy duty alternative to traditional steel safety steps is ideally suited for use in warehouses, stock rooms, high access points with machinery, airports, gymnasiums and other areas where safe, guarded high level access is required. Featuring wide steps, a sturdy 1.0m guardrail and a large aluminium working platform permit the user to work in a comfortable, safe way & this product therefore meets all needs for Work at Height. Featuring a safe braking system deployed automatically when the ladder is opened for use, but allowing transit when the ladder is moved with the raising arms, the rubber feet allow the two sturdy rubber wheels (\varnothing 125 mm) to move effortlessly on the ground. It is additionally equipped with anti-opening/anti-closing arms that can also be used as raising arms. Castellana is tested and produced according to the European Standard En131.



CAPACITY
150 KG

Easy positioning



Easy folding for transportation

Quality braking system



Tool shelf

Non-skid step: 10 cm large

TECHNICAL FEATURES

- Sturdy 100mm width safety steps are re strongly welded to the frame
- Distance between steps: 240mm
- Guardrail height: 1.0m
- Profiles dimensions: 100mm x 30mm
- Toeboard height: 150mm
- Tool shelf capacity: 15 Kg
- Rubber feet and rubber wheels (\varnothing wheels 125 mm)
- Platform in ribbed aluminium 53x67 cm
- Inner front width : 600mm

ISO9000UNIEN2071
ENISO90012

GUARANTEE
5 YEARS

n.	m	m	m	Kg	cm			
4	1,07	2,07	3,07	27,00	1,01x1,32			
6	1,60	2,60	3,60	31,00	1,01x1,60			
8	2,15	3,15	4,15	35,00	1,17x1,92			
10	2,65	3,65	4,65	39,00	1,17x2,20			
11	2,90	3,90	4,90	41,00	1,33x2,37			
12	3,16	4,16	5,16	44,00	1,33x2,50			
14	3,75	4,75	5,75	48,00	1,50x2,80			
15	3,90	4,90	5,90	50,00	1,50x2,95			

Technical features are indicative and can be modified without prior notice

On request:

- Special sizes and structures
- Kit of 4 blocking pivoting wheels
- Steps 20 cm wide
- Backside perpendicular to the ground (without EN 131)
- Short stabiliser (75 cm long) for use in confined spaces
- Non-closing fixed ladder
- Safety handrail to close the platform 360° (extra-price)

